

Bodaq Water-Based Primer Instructions

Overview:

The Bodaq Water-Based Primer is an adhesion promoter specially designed to seal a variety of surfaces and enhance the bond strength with Bodaq Architectural Films. The primer is supplied in a concentrated form and requires dilution with water before application.

Dilution Guidelines

Standard Surfaces:

- For most surface applications, mix the primer at a 50/50 ratio with water.

Porous Surfaces (e.g., MDF):

- For more absorbent materials like MDF, use a stronger dilution of 70/30 primer to water to ensure proper adhesion without over-saturation.

Application Process

Applying the Primer:

- Use a brush or lint-free roller to apply a thin coat of the diluted primer to the surface.
- Ensure an even and smooth application without bubbles, streaks, or runs. If any inconsistencies or rough areas appear, sand them down until smooth before applying the Bodaq Film.

Using Primer on Different Surfaces:

- For drywall and compound, the primer can be applied after sanding the surface smooth. While it seals and prepares the drywall, a paint primer is recommended first to highlight any flaws in the substrate that may need fixing before applying the Bodaq Film.
- Substrates like metal (excluding copper), acrylic, plastics, and glass generally do not require the use of Bodaq Primer for film application.

Safety & Technical Information

For further information on handling, safety, and technical details, please refer to the Material Safety Data Sheet (MSDS) available on our website.

[View Technical Bulletins Here](#)